USSN: 09/824,716

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

## LISTING OF CLAIMS:

1. (previously presented): A method of combining at least two received signals (A, A') of a telecommunication system comprising:

processing a first combining algorithm (B1) for providing a resulting signal (S1), and a second, differing combining algorithm (B2) for providing a second resulting signal (S2); and combining the two resulting signals (S1 and S2), wherein the combination depends on the two resulting signals (S1, S2).

- 2. (previously presented): The method of claim 1, wherein a quality of the two resulting signals (S1, S2) is estimated.
- 3. (previously presented): The method of claim 2, wherein the estimated quality of the two resulting signals (S1, S2) is used to weight the combination of the two resulting signals (S1 and S2).
- 4. (original): The method of one of claims 1 to 3, wherein one of the two algorithms (B1) is a temporal reference algorithm and the other one of the two algorithms (B2) is a spatial reference algorithm.

1 1

AMENDMENT UNDER 37 C.F.R. § 1.111

USSN: 09/824,716

The method of one of claims 1 to 4, wherein more 5. (previously presented): than two, differing algorithms (B1, B2) are used.

6. (previously presented): A receiver of a telecommunication system for combining at least two received signals (A, A') comprising:

a first combining algorithm (B1) for providing a resulting signal (S1), and a second, differing combining algorithm (B2) for providing a second resulting signal (S2); and

means for combining the two resulting signals (S1 and S2), wherein the combination depends on the two resulting signals (S1, S2).

7. (currently amended): A method of combining a plurality of received signals of a telecommunication system comprising:

receiving the plurality of signals;

determining the condition of the signals;

selecting from a plurality of differing algorithms, one or more algorithms to process the plurality of the signals, based on the condition of the signals; and

combining the processed signals selecting one of the processed signals as a representative signal.

8. A method of combining a plurality of received (previously presented): signals of a telecommunication system comprising:

receiving the plurality of signals;

, i

USSN: 09/824,716

determining the condition of the signals;

processing the plurality of signals with a plurality of algorithms based on the condition of the signals; and

selecting one of the processed signals as a representative resulting signal.

9. (currently amended): A receiver of a telecommunication system for combining a plurality of signals, comprising:

a plurality of differing algorithms;

a selector operable to select one or more of the differing algorithms to process the plurality of the signals, based on the condition of the signals; and

means for combining the processed signals or selecting one of the processed signals as a representative signal.